

**GENERAL NOTES:**


- For additional information contact Gibraltar, Inc. at 1-833-715-0810 or see the manufacturer's product manual.
- All concrete shall be per specification; minimum 17.2MPa (2500psi).
- The Cable Barrier System shall be installed on shoulders or on medians with slopes of 6:1 or flatter. If installed on slopes steeper than 6:1 up to 4:1 the TL-4 system performs as a TL-3 and Gibraltar must be contacted for various guidelines related to placement.
- The Cable Barrier System is accepted by the FHWA Test Level - 4.
- See the specification for delineation.
- Rock Clause: Where solid rock is encountered:
  - For socketed post, continue digging 305mmØ, 381mm deep into rock or the required plan depth, whichever comes first.
  - For driven post, core drill a 102mmØ hole 457mm deep into rock or the required plan depth, whichever comes first.
  - For Anchor post, continue digging 610mmØ, 762mm deep into rock or the required plan depth, whichever comes first.
- Tolerances:
  - Linepost = 76mm(max) out of plumb, at top
  - Cable height= ±25.4mm
  - Anchor Post ± 127mm off of Cable Reference Line
- The Gibraltar cable barrier system shall be installed in NCHRP Report 350 standard compacted soil. Soil must be well drained.
- All non-welded rebar by others.
- Minimum recommended line post foundation.
  - Without mowstrip, 914mm deep x 305mmØ foundations with 10M rebar ring x 203mmØ with 2-15M rebar vertical bars 762mm long or 762mm welded rebar socket.
  - With 102mm minimum depth hot mix asphalt, 762mm deep x 305mmØ foundations with 10M rebar ring x 203mmØ with 2-15M rebar vertical bars 762mm long or 762mm welded rebar socket.
  - With 76mm minimum depth concrete mowstrip, 610mm deep x 305mmØ foundations. (No rebar required).
  - Direct drive driven post and driven socket 1067mm deep.

°C	kg of Force
-23.3 °C	3629
-17.8 °C	3447
-12.2 °C	3266
-6.6 °C	3084
-1.1 °C	2903
4.4 °C	2722
10 °C	2540
15.6 °C	2359
21.1 °C	2177
26.7 °C	1996
32.2 °C	1814
37.7 °C	1633
43.3°C	1452

**C-Section Post**

Deflection	
Deflection	Post Spacing
2.82M	9.14M
2.44M	6.10M
2.03M	3.05M

**PROPRIETARY TO GIBRALTAR** Chart +/- 10%



**TL-3 Cable System Layout**

Gibraltar Cable Barrier Systems

Scale: <b>NTS</b>	Date: <b>10-18-17</b>
Layout: <b>ANSI B</b>	Drafter: <b>BH</b>